



DESCRIPTION

The GAD GT-601™ is a two-way bass reflex loudspeaker system featuring flat frequency response, low distortion and wide dynamic range. Designed for permanent and semi-permanent applications.

The GT-601™ is available with several installations choices including 3/8"-16 threaded mounting points, a U-bracket or a swivel Multimount™.



APPLICATION

The GT-601™ is designed for near-field application where a smooth, dynamic range is needed. The GT-601™ is an ideal choice for either analog or digital reproductions where clear, clean response is a must. The GT-601™ boasts wide-range dispersion for portable A/V events or even for side-fill or delay monitoring applications.

SPECIFICATIONS DATA

Frequency Response (1 watt @ 1M)	±3 db 65 Hz 20 kHz
Sensitivity (1 watt @ 1M)	(2.83V) 95 db SPL
Power Handling	AES standard 90 watts
Nominal Impedance	8 ohm
Dispersion	Horizontal 90° Vertical 40°
Cabinet Type	Multi-Angle
Finish	Black Spatter
Connectors	5-way binder
Grille	Powder-Coated, Perforated Steel
Crossover Frequency	4 kHz with 18 db per octave slope
Components	LF: 6" cone MF: n/a HF: 1" compression driver

Dimensions	Inches		Millimeters	
	Height	Width	Depth	
	11.75"	8.88"	8.75"	
Weight	Pounds		Kilograms	
	Net Weight	19		8.62

grundorf
corp.™

712-322-3900
FAX 712-322-3407

Visit us online at www.grundaudio.com
Email: sales@grundaudio.com
721 Ninth Avenue - Council Bluffs, IA 51501