



Technical Specifications

The Grund Audio Design VIP Series sets a new standard for 3-way speakers. It's design provides the user multiple applications and plenty of power handling capability in a compact, three-way, cabinet design. These full-range loudspeakers

are ideal for applications requiring high quality sound with detailed definition. The box design allows vocal optimizing and full music power capability.

The versatile VIP Series may be used in a wide-variety of commercial applications: conference rooms, dance studios, educational facilities, lounges, juke box playback systems, house of worship, karaoke systems, and restaurants.

- Large voice coils on the low frequency
- Mid-range with 1" coils, quasi horn loaded
- High frequency has 1" coils
- Multi mounting points on the back
- Comes in mirror imaged pairs
- Name badges rotate for vertical or horizontal positioning
- High power capabilities
- Highest sensitivity of SPL in its class
- Sleek, modern design and appearance
- Steel, matte black, powered-coated grilles



VIP-6

Specifications

Components	LF: 6.5" Cone HF: 1" Dome Tweeter
Frequency Response:	68Hz - 20KHz
Sensitivity:	90 dB
Power Handling RMS:	60 Watt
Power Handling Program:	120 Watt
Nominal Impedance:	8 ohm
Enclosure Type:	Multi-angle
Enclosure Material:	Textured Plastic
Grille:	Powder-Coated, Perforated Steel
Dimensions (HxWxD):	12.25" x 8.13" x 8.25"
Weight:	311.15 mm x 206.502 mm x 209.55 mm 7.6 lbs 3.04 Kg



VIP-8

Specifications

Components	LF: 8" Cone MF: 5" Cone HF: 1" Dome Tweeter
Frequency Response:	45Hz - 18KHz
Sensitivity:	95 dB
Power Handling RMS:	120 Watt
Power Handling Program:	240 Watt
Nominal Impedance:	8 ohm
Enclosure Type:	Multi-angle
Enclosure Material:	Textured Plastic
Grille:	Powder-Coated, Perforated Steel
Dimensions (HxWxD):	15.7" x 10" x 10"
Weight:	398.78 mm x 254 mm x 254 mm 15.4 lbs 6.16 Kg



VIP-10

Specifications

Components	LF: 10" Cone MF: 5" Cone HF: 1" Dome Tweeter
Frequency Response:	40Hz - 18KHz
Sensitivity:	97 dB
Power Handling RMS:	200 Watt
Power Handling Program:	400 Watt
Nominal Impedance:	8 ohm
Enclosure Type:	Multi-angle
Enclosure Material:	Textured Plastic
Grille:	Powder-Coated, Perforated Steel
Dimensions (HxWxD):	19.5" x 12.25" x 11"
Weight:	495.3 mm x 311.15 mm x 279.4 mm 20.9 lbs 8.36 Kg



VIP-12

Specifications

Components	LF: 12" Cone MF: 5" Cone HF: 1" Dome Tweeter
Frequency Response:	38Hz - 18KHz
Sensitivity:	98 dB
Power Handling RMS:	250 Watt
Power Handling Program:	500 Watt
Nominal Impedance:	8 ohm
Enclosure Type:	Multi-angle
Enclosure Material:	Textured Plastic
Grille:	Powder-Coated, Perforated Steel
Dimensions (HxWxD):	20.5" x 13.25" x 11.88"
Weight:	520.7mm x 336.55mm x 301.752mm 25.7 lbs 10.28 Kg



Technical Specifications



VIP-12S-200

Specifications

Components	LF: 12 Cone
Frequency Response:	45 Hz - 250 Hz
Sensitivity:	93 dB
Power Handling RMS:	200 Watt
Power Handling Program:	400 Watt
Nominal Impedance:	8 ohm
Dispersion:	Omni-Directional
Enclosure Type:	Rectangle
Enclosure Material:	Textured Plastic
Grille:	Powder-Coated, Perforated Steel
Connectors:	2 Standard RCA
Dimensions (HxWxD):	H - 13.78" W - 20.08" D - 16.14"
	H - 350.01 W - 510.03 D - 409.96
Weight:	69.9 Lbs / 31.5 Kgs



VIP-15S-350

Specifications

Components	LF: 15" Cone
Frequency Response:	45 Hz - 250 Hz
Sensitivity:	95 dB
Power Handling RMS:	350 Watt
Power Handling Program:	700 Watt
Nominal Impedance:	8 ohm
Dispersion:	Omni-Directional
Enclosure Type:	Rectangle
Enclosure Material:	Textured Plastic
Grille:	Powder-Coated, Perforated Steel
Connectors:	2 Standard RCA
Dimensions (HxWxD):	17.72" x 27.17" x 20.67"
	450.1mm x 690.1mm x 525.0mm
Weight:	94.5 Lbs / 42.5 Kgs

